






# MACROLUX




Article code	Article	Colour	Light Temperature (°K)	Watt (W)	Length (mm)
134.0112.00.92	MD_12-92 L=max 3 m	Black (92)			
134.0112.01.92	MD_12/3000-92 L=3m - EMPTY STANDARD	Black (92)			3000
134.0112.01.M10.92	MD_12/3000-92 L=3m - 10x EMPTY STANDARD	Black (92)			3000
134.0112.120.2700.92	MD_12/2x9.6W/2700°K-92 L=max 3 m	Black (92)	2700	19,6	
134.0112.120.4000.92	MD_12/2x9.6W/4000°K-92 L=max 3 m	Black (92)	4000	19,6	
134.0112.120.92	MD_12/2x9.6W/3000°K-92 L=max 3 m	Black (92)	3000	19,6	
134.0112.240.2700.92	MD_12/2x19.6W/2700°K-92 L=max 3 m	Black (92)	2700	39,2	
134.0112.240.4000.92	MD_12/2x19.6W/4000°K-92 L=max 3 m	Black (92)	4000	39,2	
134.0112.240.92	MD_12/2x19.6W/3000°K-92 L=max 3 m	Black (92)	3000	39,2	




Article code	Article	Colour	Light Temperature (°K)	Watt (W)	Length (mm)
134.0112.00.94	MD_12-94 L=max 3 m	White (94)			
134.0112.01.94	MD_12/3000-94 L=3m - EMPTY STANDARD	White (94)			3000
134.0112.01.M10.94	MD_12/3000-94 L=3m - 10x EMPTY STANDARD	White (94)			3000
134.0112.120.2700.94	MD_12/2x9.6W/2700°K-94 L=max 3 m	White (94)	2700	19,6	
134.0112.120.4000.94	MD_12/2x9.6W/4000°K-94 L=max 3 m	White (94)	4000	19,6	
134.0112.120.94	MD_12/2x9.6W/3000°K-94 L=max 3 m	White (94)	3000	19,6	
134.0112.240.2700.94	MD_12/2x19.6W/2700°K-94 L=max 3 m	White (94)	2700	39,2	
134.0112.240.4000.94	MD_12/2x19.6W/4000°K-94 L=max 3 m	White (94)	4000	39,2	
134.0112.240.94	MD_12/2x19.6W/3000°K-94 L=max 3 m	White (94)	3000	39,2	



Article code	Name	Description
1324.0000	STRIP LED/Primer monouso 0,66 ml	
1324.0000.10	STRIP LED/Primer monouso 0,66 ml - 10 PZ	



Article code	Name	Description	Colour
134.5112.92	MD_12/TC-92	Testata di chiusura, finitura nero / End cap, finishing black (1 pz.)	Black (92)
134.5112.92.10	MD_12/TC-92 - 10 PZ	Testata di chiusura, finitura nero / End cap, finishing black (10 pz.)	Black (92)



Article code	Name	Description	Colour
134.5112.94	MD_12/TC-94	Testata di chiusura, finitura bianco / End cap, finishing white (1 pz.)	White (94)
134.5112.94.10	MD_12/TC-94 - 10 PZ	Testata di chiusura, finitura bianco / End cap, finishing white (10 pz.)	White (94)




Article code	Name	Description
134.2112	MD_12/G090 (Solo taglio)	Connessione ad angolo orizzontale 90°


200 x 200

Powered by HTML.COM


Article code	Name	Description
134.1112	MD_12/G0270 (Solo taglio)	Connessione ad angolo orizzontale 270°




Article code	Name	Description
1320.1112	UNIVERSALE M_12 / MB_15	Ancoraggio plafone / giunto lineare - Compatibile con MTO_12, MT1_12, MX1_12 e MB_15
1320.1112.10	UNIVERSALE M_12/MB_15 - 10 PZ	Ancoraggio plafone / giunto lineare




Article code	Name	Description	Watt (W)	Driver's type
1.024015	Driver LED 24V 15W IP20		15	On/Off




Article code	Name	Description	Watt (W)	Driver's type
1.024020	Driver LED 24V 20W IP20		20	On/Off




Article code	Name	Description	Watt (W)	Driver's type
1.024036	Driver LED 24V 36W IP40		36	On/Off




Article code	Name	Description	Watt (W)	Driver's type
1.024060C	Driver LED 24V 60W IP40		60	On/Off




Article code	Name	Description	Watt (W)	Driver's type
1.024075	Driver LED 24V 75W IP20		75	On/Off



Article code	Name	Description	Watt (W)	Driver's type
1.97759	Driver LED 24V 150W IP67		150	On/Off



Article code	Name	Description	Watt (W)	Driver's type
1.97745	Driver LED 24V 200W IP67	Dimensioni 69 x 37 x 206 mm	200	On/Off



Article code	Name	Description	Length (mm)
1312.9112.01	ML_12/Diffusore Opale L=3m - EMPTY STANDARD	Profilo PC / Compatibile con MA_12 - Senza taglio a misura	3000