

MACROLUX

mt3_27









Article code	Article	Colour	Diffuser	Light Temperature (°K)	Watt (W)	Length (mm)
1320.0327.00.98	MT3_27/DO-98 L=max 3 m	Grey anodize (98)	Opal			
1320.0327.01.98	MT3_27/DO/3000-98 L=3m - EMPTY STANDARD	Grey anodize (98)	Opal			3000
1320.0327.01.M10.98	MT3_27/DO/3000-98 L=3M - 10x EMPTY STANDARD	Grey anodize (98)	Opal			3000
1320.0327.120.2700.98	MT3_27/9,6W/2700°K-98	Grey anodize (98)	Opal	2700	9,6	
1320.0327.120.4000.98	mt3_27/4000-98#	Grey anodize (98)	Opal	4000	9,6	
1320.0327.120.98	mt3_27/3000-98#	Grey anodize (98)	Opal	3000	9,6	
1320.0327.240.2700.98	MT3_27/19.6W/2700°K-98	Grey anodize (98)	Opal	2700	19,6	
1320.0327.240.4000.98	MT3_27/18,5W/4000°K-98	Grey anodize (98)	Opal	4000	19,6	
1320.0327.240.98	MT3_27/19.6W/3000°K-98	Grey anodize (98)	Opal	3000	19,6	
1320.03279.01.98	MT3_27/DP/3000-98 L=3m - EMPTY STANDARD	Grey anodize (98)	Prismatic			3000
1320.03279.01.M10.98	MT3_27/DP/3000-98 L=3M - 10x EMPTY STANDARD	Grey anodize (98)	Prismatic			3000









Article code	Article	Colour	Diffuser	Light Temperature (°K)	Watt (W)	Length (mm)
1320.0327.00.92	MT3_27/DO-92 L=max 3 m	Black (92)	Opal			
1320.0327.01.92	MT3_27/DO/3000-92 L=3m - EMPTY STANDARD	Black (92)	Opal			3000
1320.0327.01.M10.92	MT3_27/DO/3000-92 L=3M - 10x EMPTY STANDARD	Black (92)	Opal			3000
1320.0327.120.2700.92	MT3_27/9,6W/2700°K-92	Black (92)	Opal	2700	9,6	
1320.0327.120.4000.92	MT3_27/9,6W/4000°K-92	Black (92)	Opal	4000	9,6	
1320.0327.120.92	MT3_27/9,6W/3000°K-92	Black (92)	Opal	3000	9,6	
1320.0327.240.2700.92	MT3_27/19.6W/2700°K-92	Black (92)	Opal	2700	19,6	
1320.0327.240.4000.92	MT3_27/18,5W/4000°K-92	Black (92)	Opal	4000	19,6	
1320.0327.240.92	MT3_27/19.6W/3000°K-92	Black (92)	Opal	3000	19,6	
1320.03279.01.92	MT3_27/DP/3000-92 L=3m - EMPTY STANDARD	Black (92)	Prismatic			3000
1320.03279.01.M10.92	MT3_27/DP/3000-92 L=3M - 10x EMPTY STANDARD	Black (92)	Prismatic			3000









Article code	Article	Colour	Diffuser	Light Temperature (°K)	Watt (W)	Length (mm)
1320.0327.00.94	MT3_27/DO-94 L=max 3 m	White (94)	Opal			
1320.0327.01.94	MT3_27/DO/3000-94 L=3m - EMPTY STANDARD	White (94)	Opal			3000


Article code	Article	Colour	Diffuser	Light Temperature (°K)	Watt (W)	Length (mm)
1320.0327.01.M10.94	MT3_27/DO/3000-94 L=3M - 10x EMPTY STANDARD	White (94)	Opal			3000
1320.0327.120.2700.94	MT3_27/9,6W/2700°K-94	White (94)	Opal	2700	9,6	
1320.0327.120.4000.94	MT3_27/DO/9,6W/4000°K-94	White (94)	Opal	4000	9,6	
1320.0327.120.94	MT3_27/9,6W/3000°K-94	White (94)	Opal	3000	9,6	
1320.0327.240.2700.94	MT3_27/19.6W/2700°K-94	White (94)	Opal	2700	19,6	
1320.0327.240.4000.94	MT3_27/19.6W/4000°K-94	White (94)	Opal	4000	19,6	
1320.0327.240.94	MT3_27/19.6W/3000°K-94	White (94)	Opal	3000	19,6	
1320.03279.01.94	MT3_27/DP/3000-94 L=3m - EMPTY STANDARD	White (94)	Prismatic			3000
1320.03279.01.M10.94	MT3_27/DP/3000-94 L=3M - 10x EMPTY STANDARD	White (94)	Prismatic			3000




Article code	Name	Description
1324.0000	STRIP LED/Primer monouso 0,66 ml	
1324.0000.10	STRIP LED/Primer monouso 0,66 ml - 10 PZ	




Article code	Name	Description	Watt (W)	Driver's type
1.024015	Driver LED 24V 15W IP20		15	On/Off




Article code	Name	Description	Watt (W)	Driver's type
1.024020	Driver LED 24V 20W IP20		20	On/Off




Article code	Name	Description	Watt (W)	Driver's type
1.024036	Driver LED 24V 36W IP40		36	On/Off




Article code	Name	Description	Watt (W)	Driver's type
1.024060C	Driver LED 24V 60W IP40		60	On/Off




Article code	Name	Description	Watt (W)	Driver's type
1.024075	Driver LED 24V 75W IP20		75	On/Off




Article code	Name	Description	Watt (W)	Driver's type
1.97759	Driver LED 24V 150W IP67		150	On/Off




Article code	Name	Description	Watt (W)	Driver's type
1.97745	Driver LED 24V 200W IP67	Dimensioni 69 x 37 x 206 mm	200	On/Off




Article code	Name	Description	Watt (W)	Light Temperature (°K)	Length (mm)
1310.27.300	MKT_27/300/7,5W/3000°K	Profilo alluminio L=300 mm 7,5W 24V 950lm 3000°K CRI>90 - Driver escluso	7,5	3000	300




Article code	Name	Description	Watt (W)	Light Temperature (°K)	Length (mm)
1310.27.600	MKT_27/600/15W/3000°K	Profilo alluminio L=600 mm 15W 24V 1900lm 3000°K CRI>90 - Driver escluso	15	3000	600



Article code	Name	Description	Watt (W)	Light Temperature (°K)	Length (mm)
1310.27.900	MKT_27/900/22,5W/3000°K	Profilo alluminio L=900 mm 22,5W 24V 2850lm 3000°K CRI>90 - Driver escluso	22.5	3000	900




Article code	Name	Description	Watt (W)	Light Temperature (°K)	Length (mm)
1310.27.1200	MKT_27/1200/30W/3000°K	Profilo alluminio L=1200 mm 30W 24V 3800lm 3000°K CRI>90 - Driver escluso	30	3000	1200




Article code	Name	Description	Watt (W)	Light Temperature (°K)	Length (mm)
1310.27.1500	MKT_27/1500/37,5W/3000°K	Profilo alluminio L=1500 mm 37,5W 24V 4750lm 3000°K CRI>90 - Driver escluso	37.5	3000	1500




Article code	Name	Description	Length (mm)
1310.27.00	MKT_27/CA	Cavo 24V di alimentazione L=500 mm	500




Article code	Name	Description	Colour
1320.5327.98	MT3_27/TC-98	Testata di chiusura, finitura grigio alluminio/ End cap, finishing grey aluminium	Grey anodize (98)
1320.5327.98.10	MT3_27/TC-98 - 10 PZ	Testata di chiusura, finitura grigio alluminio	Grey anodize (98)




Article code	Name	Description	Colour
1320.5327.94	MT3_27/TC-4	Testata di chiusura, finitura bianco / End cap, finishing white (1 pz.)	White (94)
1320.5327.94.10	MT3_27/TC-4 - 10 PZ	Testata di chiusura, finitura bianco / End cap, finishing white	White (94)



Article code	Name	Description	Colour
1320.5327.92	MT3_27/TC-2	Testata di chiusura, finitura nero / End cap, finishing black (1 pz.)	Black (92)
1320.5327.92.10	MT3_27/TC-2 - 10 PZ	Testata di chiusura, finitura nero / End cap, finishing nero	Black (92)



Article code	Name	Description
1324.9127.01	M_27/Diffusore Opale L=3m - EMPTY STANDARD	Profilo PC Opale / Compatibile con MX0_27, MT1_27, MT3_27 - Senza taglio a misura



Article code	Name	Description
1324.91279.01	M_27/Diffusore Prismatizzato L=3m - EMPTY STANDARD	Profilo PC Prismatizzato / Compatibile con MX0_27, MT1_27, MT3_27 - Senza taglio a misura