





# MACROLUX



Codice Articolo	Articolo	Colore	Temperatura Luce (°K)	Lunghezza (mm)	Tipo Lente	Potenza (W)
2211.1145.01.07.92	WL/PL/1145/M60°/3000°K-92	Nero (92)	3000	1145	Medium 60° UGR	22
2211.1145.01.4000.07.92	WL/PL/1145/M60°/4000°K-92	Nero (92)	4000	1145	Medium 60° UGR	22
2211.1145.08.07.92	WL/PL/1145/M60°/3000°K-92 DALI/PUSH	Nero (92)	3000	1145	Medium 60° UGR	22
2211.1145.08.4000.07.92	worklife surface mounted/1145/4000-92#	Nero (92)	4000	1145	Medium 60° UGR	22
2211.1704.01.07.92	WL/PL/1704/M60°/3000°K-92	Nero (92)	3000	1704	Medium 60° UGR	33
2211.1704.01.4000.07.92	WL/PL/1704/M60°/4000°K-92	Nero (92)	4000	1704	Medium 60° UGR	33
2211.1704.08.07.92	WL/PL/1704/M60°/3000°K-92 DALI/PUSH	Nero (92)	3000	1704	Medium 60° UGR	33
2211.1704.08.4000.07.92	worklife surface mounted/1704/4000-92#	Nero (92)	4000	1704	Medium 60° UGR	33
2211.2263.01.07.92	WL/PL/2263/M60°/3000°K-92	Nero (92)	3000	2263	Medium 60° UGR	44
2211.2263.01.4000.07.92	WL/PL/2263/M60°/4000°K-92	Nero (92)	4000	2263	Medium 60° UGR	44
2211.2263.08.07.92	WL/PL/2263/M60°/3000°K-92 DALI/PUSH	Nero (92)	3000	2263	Medium 60° UGR	44
2211.2263.08.4000.07.92	worklife surface mounted/2263/4000-92#	Nero (92)	4000	2263	Medium 60° UGR	44
2211.2822.01.07.92	WL/PL/2822/M60°/3000°K-92	Nero (92)	3000	2822	Medium 60° UGR	55
2211.2822.01.4000.07.92	WL/PL/2822/M60°/4000°K-92	Nero (92)	4000	2822	Medium 60° UGR	55
2211.2822.08.07.92	WL/PL/2822/M60°/3000°K-92 DALI/PUSH	Nero (92)	3000	2822	Medium 60° UGR	55
2211.2822.08.4000.07.92	WL/PL/2822/M60°/4000°K-92 DALI/PUSH	Nero (92)	4000	2822	Medium 60° UGR	55



Codice Articolo	Articolo	Colore	Temperatura Luce (°K)	Lunghezza (mm)	Tipo Lente	Potenza (W)
2211.1145.01.07.94	WL/PL/1145/M60°/3000°K-94	Bianco (94)	3000	1145	Medium 60° UGR	22
2211.1145.01.4000.07.94	WL/PL/1145/M60°/4000°K-94	Bianco (94)	4000	1145	Medium 60° UGR	22
2211.1145.08.07.94	WL/PL/1145/M60°/3000°K-94 DALI/PUSH	Bianco (94)	3000	1145	Medium 60° UGR	22
2211.1145.08.4000.07.94	worklife surface mounted/1145/4000-94#	Bianco (94)	4000	1145	Medium 60° UGR	22
2211.1704.01.07.94	WL/PL/1704/M60°/3000°K-94	Bianco (94)	3000	1704	Medium 60° UGR	33
2211.1704.01.4000.07.94	WL/PL/1704/M60°/4000°K-94	Bianco (94)	4000	1704	Medium 60° UGR	33
2211.1704.08.07.94	WL/PL/1704/M60°/3000°K-94 DALI/PUSH	Bianco (94)	3000	1704	Medium 60° UGR	33
2211.1704.08.4000.07.94	worklife surface mounted/1704/4000-94#	Bianco (94)	4000	1704	Medium 60° UGR	33
2211.2263.01.07.94	WL/PL/2263/M60°/3000°K-94	Bianco (94)	3000	2263	Medium 60° UGR	44
2211.2263.01.4000.07.94	worklife surface mounted/2263/4000-94#	Bianco (94)	4000	2263	Medium 60° UGR	44
2211.2263.08.07.94	WL/PL/2263/M60°/3000°K-94 DALI/PUSH	Bianco (94)	3000	2263	Medium 60° UGR	44
2211.2263.08.4000.07.94	worklife surface mounted/2263/4000-94#	Bianco (94)	4000	2263	Medium 60° UGR	44
2211.2822.01.07.94	WL/PL/2822/M60°/3000°K-94	Bianco (94)	3000	2822	Medium 60° UGR	55
2211.2822.01.4000.07.94	WL/PL/2822/M60°/4000°K-94	Bianco (94)	4000	2822	Medium 60° UGR	55
2211.2822.08.07.94	WL/PL/2822/M60°/3000°K-94 DALI/PUSH	Bianco (94)	3000	2822	Medium 60° UGR	55
2211.2822.08.4000.07.94	worklife surface mounted/2822/4000-94#	Bianco (94)	4000	2822	Medium 60° UGR	55