




# MACROLUX



Codice Articolo	Articolo	Colore	Emissione (°)	Temperatura Luce (°K)	Potenza (W)	Lunghezza (mm)	UGR
82.1400.01.4000.92	*HB/S/1410/64W/4000°K-92 DALI	Nero (92)	54	4000	64	1410	UGR<19
82.1400.01.92	HB/S/1410/64W/3000°K-92 DALI	Nero (92)	54	3000	64	1410	UGR<19
82.1400.02.4000.92	*HB/S/1410/64W/4000°K-92 PUSH	Nero (92)	54	4000	64	1410	UGR<19
82.1400.02.92	HB/S/1410/64W/3000°K-92 PUSH	Nero (92)	54	3000	64	1410	UGR<19
82.1400.4000.92	*HB/S/1410/64W/4000°K-92	Nero (92)	54	4000	64	1410	UGR<19
82.1400.92	HB/S/1410/64W/3000°K-92	Nero (92)	54	3000	64	1410	UGR<19
82.1680.01.4000.92	*HB/S/1690/77W/4000°K-92 DALI	Nero (92)	54	4000	77	1680	UGR<19
82.1680.01.92	HB/S/1690/77W/3000°K-92 DALI	Nero (92)	54	3000	77	1680	UGR<19
82.1680.02.4000.92	HB/S/1690/77W/4000°K-92 PUSH	Nero (92)	54	4000	77	1680	UGR<19
82.1680.02.92	HB/S/1690/77W/3000°K-92 PUSH	Nero (92)	54	3000	77	1680	UGR<19
82.1680.4000.92	*HB/S/1690/77W/4000°K-92	Nero (92)	54	4000	77	1680	UGR<19
82.1680.92	HB/S/1690/77W/3000°K-92	Nero (92)	54	3000	77	1680	UGR<19
82.2240.01.4000.92	*HB/S/2250/103W/4000°K-92 DALI	Nero (92)	54	4000	103	2240	UGR<19
82.2240.01.92	HB/S/2250/103W/3000°K-92 DALI	Nero (92)	54	3000	103	2240	UGR<19
82.2240.02.4000.92	*HB/S/2250/103W/4000°K-92 PUSH	Nero (92)	54	4000	103	2240	UGR<19
82.2240.02.92	HB/S/2250/103W/3000°K-92 PUSH	Nero (92)	54	3000	103	2240	UGR<19
82.2240.4000.92	*HB/S/2250/103W/4000°K-92	Nero (92)	54	4000	103	2240	UGR<19
82.2240.92	HB/S/2250/103W/3000°K-92	Nero (92)	54	3000	103	2240	UGR<19



Codice Articolo	Articolo	Colore	Emissione (°)	Temperatura Luce (°K)	Potenza (W)	Lunghezza (mm)	UGR
82.1400.01.4000.94	*HB/S/1410/64W/4000°K-94 DALI	Bianco (94)	54	4000	64	1410	UGR<19
82.1400.01.94	*HB/S/1410/64W/3000°K-94 DALI	Bianco (94)	54	3000	64	1410	UGR<19
82.1400.02.4000.94	*HB/S/1410/64W/4000°K-94 PUSH	Bianco (94)	54	4000	64	1410	UGR<19
82.1400.02.94	*HB/S/1410/64W/3000°K-94 PUSH	Bianco (94)	54	3000	64	1410	UGR<19
82.1400.4000.94	HB/S/1410/64W/4000°K-94	Bianco (94)	54	4000	64	1410	UGR<19
82.1400.94	HB/S/1410/64W/3000°K-94	Bianco (94)	54	3000	64	1410	UGR<19
82.1680.01.4000.94	*HB/S/1690/77W/4000°K-94 DALI	Bianco (94)	54	4000	77	1680	UGR<19
82.1680.01.94	HB/S/1690/77W/3000°K-94 DALI	Bianco (94)	54	3000	77	1680	UGR<19
82.1680.02.4000.94	*HB/S/1690/77W/4000°K-94 PUSH	Bianco (94)	54	4000	77	1680	UGR<19
82.1680.02.94	HB/S/1690/77W/3000°K-94 PUSH	Bianco (94)	54	3000	77	1680	UGR<19
82.1680.4000.94	*HB/S/1690/77W/4000°K-94	Bianco (94)	54	4000	77	1680	UGR<19
82.1680.94	HB/S/1690/77W/3000°K-94	Bianco (94)	54	3000	77	1680	UGR<19
82.2240.01.4000.94	*HB/S/2250/103W/4000°K-94 DALI	Bianco (94)	54	4000	103	2240	UGR<19
82.2240.01.94	HB/S/2250/103W/3000°K-94 DALI	Bianco (94)	54	3000	103	2240	UGR<19
82.2240.02.4000.94	*HB/S/2250/103W/4000°K-94 PUSH	Bianco (94)	54	4000	103	2240	UGR<19
82.2240.02.94	HB/S/2250/103W/3000°K-94 PUSH	Bianco (94)	54	3000	103	2240	UGR<19
82.2240.4000.94	*HB/S/2250/103W/4000°K-94	Bianco (94)	54	4000	103	2240	UGR<19
82.2240.94	*HB/S/2250/103W/3000°K-94	Bianco (94)	54	3000	103	2240	UGR<19



Codice Articolo	Articolo	Colore	Emissione (°)	Temperatura Luce (°K)	Potenza (W)	Lunghezza (mm)	UGR
82.1400.01.4000.96	*HB/S/1410/64W/4000°K-96 DALI	Bronzo (96)	54	4000	64	1410	UGR<19
82.1400.01.96	*HB/S/1410/64W/3000°K-96 DALI	Bronzo (96)	54	3000	64	1410	UGR<19
82.1400.02.4000.96	*HB/S/1410/64W/4000°K-96 PUSH	Bronzo (96)	54	4000	64	1410	UGR<19
82.1400.02.96	HB/S/1410/64W/3000°K-96 PUSH	Bronzo (96)	54	3000	64	1410	UGR<19
82.1400.4000.96	*HB/S/1410/64W/4000°K-96	Bronzo (96)	54	4000	64	1410	UGR<19
82.1400.96	HB/S/1410/64W/3000°K-96	Bronzo (96)	54	3000	64	1410	UGR<19
82.1680.01.4000.96	*HB/S/1690/77W/4000°K-96 DALI	Bronzo (96)	54	4000	77	1680	UGR<19
82.1680.01.96	HB/S/1690/77W/3000°K-96 DALI	Bronzo (96)	54	3000	77	1680	UGR<19
82.1680.02.4000.96	*HB/S/1690/77W/4000°K-96 PUSH	Bronzo (96)	54	4000	77	1680	UGR<19
82.1680.02.96	HB/S/1690/77W/3000°K-96 PUSH	Bronzo (96)	54	3000	77	1680	UGR<19
82.1680.4000.96	*HB/S/1690/77W/4000°K-96	Bronzo (96)	54	4000	77	1680	UGR<19
82.1680.96	HB/S/1690/77W/3000°K-96	Bronzo (96)	54	3000	77	1680	UGR<19
82.2240.01.4000.96	HB/S/2250/103W/4000°K-96 DALI	Bronzo (96)	54	4000	103	2240	UGR<19
82.2240.01.96	HB/S/2250/103W/3000°K-96 DALI	Bronzo (96)	54	3000	103	2240	UGR<19
82.2240.02.4000.96	*HB/S/2250/103W/4000°K-96 PUSH	Bronzo (96)	54	4000	103	2240	UGR<19
82.2240.02.96	HB/S/2250/103W/3000°K-96 PUSH	Bronzo (96)	54	3000	103	2240	UGR<19
82.2240.4000.96	*HB/S/2250/103W/4000°K-96	Bronzo (96)	54	4000	103	2240	UGR<19
82.2240.96	HB/S/2250/103W/3000°K-96	Bronzo (96)	54	3000	103	2240	UGR<19