




# MACROLUX




Article code	Article	Colour	Light Temperature (°K)	Beam angle (°)	Additional colour	Size (mm)	Watt (W)
2015.6130.08.22	TORCH/T8/ME_648/130-22 8.6W 250mA 26°	Black (2)	3000	26	Black (2)	130	8,6
2015.6130.08.2700.22	*TORCH/T8/ME_648/130-22 8.6W 250mA 26° 2700°K	Black (2)	2700	26	Black (2)	130	8,6
2015.6130.08.4000.22	TORCH/T8/ME_648/130-22 8.6W 250mA 26° 4000°K	Black (2)	4000	26	Black (2)	130	8,6
2015.6130.0810.22	TORCH/T8/ME_648/130-22 8.6W 250mA 26° DALI	Black (2)	3000	26	Black (2)	130	8,6
2015.6130.0810.2700.22	TORCH/T8/ME_648/130-22 8.6W 250mA 26° 2700°K DALI	Black (2)	2700	26	Black (2)	130	8,6
2015.6130.0810.4000.22	*TORCH/T8/ME_648/130-22 8.6W 26° 4000°K DALI	Black (2)	4000	26	Black (2)	130	8,6




Article code	Article	Colour	Light Temperature (°K)	Beam angle (°)	Additional colour	Size (mm)	Watt (W)
2015.6130.08.2700.296	*TORCH/T8/ME_648/130-296 8.6W 250mA 26° 2700°K	Black (2)	2700	26	Bronze (96)	130	8,6
2015.6130.08.296	*TORCH/T8/ME_648/130-296 8.6W 250mA 26°	Black (2)	3000	26	Bronze (96)	130	8,6
2015.6130.08.4000.296	*TORCH/T8/ME_648/130-296 8.6W 250mA 26° 4000°K	Black (2)	4000	26	Bronze (96)	130	8,6
2015.6130.0810.2700.296	*TORCH/T8/ME_648/130-296 8.6W 26° 2700°K DALI	Black (2)	2700	26	Bronze (96)	130	8,6
2015.6130.0810.296	*TORCH/T8/ME_648/130-496 8.6W 26° DALI	Black (2)	3000	26	Bronze (96)	130	8,6
2015.6130.0810.4000.296	*TORCH/T8/ME_648/130-296 8.6W 26° 4000°K DALI	Black (2)	4000	26	Bronze (96)	130	8,6




Article code	Article	Colour	Light Temperature (°K)	Beam angle (°)	Additional colour	Size (mm)	Watt (W)
2015.6130.08.2700.42	TORCH/T8/ME_648/130-42 8.6W 250mA 26° 2700°K	White (4)	2700	26	Black (2)	130	8,6
2015.6130.08.4000.42	*TORCH/T8/ME_648/130-42 8.6W 250mA 26° 4000°K	White (4)	4000	26	Black (2)	130	8,6
2015.6130.08.42	TORCH/T8/ME_648/130-42 8.6W 250mA 26°	White (4)	3000	26	Black (2)	130	8,6
2015.6130.0810.2700.42	*TORCH/T8/ME_648/130-42 8.6W 26° 2700°K DALI	White (4)	2700	26	Black (2)	130	8,6
2015.6130.0810.4000.42	*TORCH/T8/ME_648/130-42 8.6W 26° 4000°K DALI	White (4)	4000	26	Black (2)	130	8,6
2015.6130.0810.42	TORCH/T8/ME_648/130-42 8.6W 250mA 26° DALI	White (4)	3000	26	Black (2)	130	8,6




Article code	Article	Colour	Light Temperature (°K)	Beam angle (°)	Additional colour	Size (mm)	Watt (W)
2015.6130.08.2700.496	*TORCH/T8/ME_648/130-496 8.6W 250mA 26° 2700°K	White (4)	2700	26	Bronze (96)	130	8,6
2015.6130.08.4000.496	*TORCH/T8/ME_648/130-496 8.6W 250mA 26° 4000°K	White (4)	4000	26	Bronze (96)	130	8,6
2015.6130.08.496	*TORCH/T8/ME_648/130-496 8.6W 250mA 26°	White (4)	3000	26	Bronze (96)	130	8,6
2015.6130.0810.2700.496	*TORCH/T8/ME_648/130-496 8.6W 26° 2700°K DALI	White (4)	2700	26	Bronze (96)	130	8,6
2015.6130.0810.4000.496	*TORCH/T8/ME_648/130-496 8.6W 26° 4000°K DALI	White (4)	4000	26	Bronze (96)	130	8,6
2015.6130.0810.496	*TORCH/T8/ME_648/130-496 8.6W 26° DALI	White (4)	3000	26	Bronze (96)	130	8,6




Article code	Article	Colour	Light Temperature (°K)	Beam angle (°)	Additional colour	Size (mm)	Watt (W)
2015.6180.08.22	TORCH/T8/ME_648/180-22 8.6W 250mA 26°	Black (2)	3000	26	Black (2)	180	8,6
2015.6180.08.2700.22	*TORCH/T8/ME_648/180-22 8.6W 250mA 26° 2700°K	Black (2)	2700	26	Black (2)	180	8,6
2015.6180.08.4000.22	*TORCH/T8/ME_648/180-22 8.6W 250mA 26° 4000°K	Black (2)	4000	26	Black (2)	180	8,6
2015.6180.0810.22	TORCH/T8/ME_648/180-22 8.6W 250mA 26° DALI	Black (2)	3000	26	Black (2)	180	8,6
2015.6180.0810.2700.22	*TORCH/T8/ME_648/180-22 8.6W 26° 2700°K DALI	Black (2)	2700	26	Black (2)	180	8,6
2015.6180.0810.4000.22	*TORCH/T8/ME_648/180-22 8.6W 26° 4000°K DALI	Black (2)	4000	26	Black (2)	180	8,6




Article code	Article	Colour	Light Temperature (°K)	Beam angle (°)	Additional colour	Size (mm)	Watt (W)
2015.6180.08.2700.296	*TORCH/T8/ME_648/180-296 8.6W 250mA 26° 2700°K	Black (2)	2700	26	Bronze (96)	180	8,6
2015.6180.08.296	*TORCH/T8/ME_648/180-296 8.6W 250mA 26°	Black (2)	3000	26	Bronze (96)	180	8,6
2015.6180.08.4000.296	*TORCH/T8/ME_648/180-296 8.6W 250mA 26° 4000°K	Black (2)	4000	26	Bronze (96)	180	8,6
2015.6180.0810.2700.296	*TORCH/T8/ME_648/180-296 8.6W 26° 2700°K DALI	Black (2)	2700	26	Bronze (96)	180	8,6
2015.6180.0810.296	TORCH/T8/ME_648/180-296 8.6W 250mA 26° DALI	Black (2)	3000	26	Bronze (96)	180	8,6
2015.6180.0810.4000.296	*TORCH/T8/ME_648/180-296 8.6W 26° 4000°K DALI	Black (2)	4000	26	Bronze (96)	180	8,6



Article code	Article	Colour	Light Temperature (°K)	Beam angle (°)	Additional colour	Size (mm)	Watt (W)
2015.6180.08.2700.42	*TORCH/T8/ME_648/180-42 8.6W 250mA 26° 2700°K	White (4)	2700	26	Black (2)	180	8,6
2015.6180.08.4000.42	*TORCH/T8/ME_648/180-42 8.6W 250mA 26° 4000°K	White (4)	4000	26	Black (2)	180	8,6
2015.6180.08.42	*TORCH/T8/ME_648/180-42 8.6W 250mA 26°	White (4)	3000	26	Black (2)	180	8,6
2015.6180.0810.2700.42	*TORCH/T8/ME_648/180-42 8.6W 26° 2700°K DALI	White (4)	2700	26	Black (2)	180	8,6
2015.6180.0810.4000.42	*TORCH/T8/ME_648/180-42 8.6W 26° 4000°K DALI	White (4)	4000	26	Black (2)	180	8,6
2015.6180.0810.42	TORCH/T8/ME_648/180-42 8.6W 250mA 26° DALI	White (4)	3000	26	Black (2)	180	8,6



Article code	Article	Colour	Light Temperature (°K)	Beam angle (°)	Additional colour	Size (mm)	Watt (W)
2015.6180.08.2700.496	*TORCH/T8/ME_648/180-496 8.6W 250mA 26° 2700°K	White (4)	2700	26	Bronze (96)	180	8,6
2015.6180.08.4000.496	*TORCH/T8/ME_648/180-496 8.6W 250mA 26° 4000°K	White (4)	4000	26	Bronze (96)	180	8,6
2015.6180.08.496	*TORCH/T8/ME_648/180-496 8.6W 250mA 26°	White (4)	3000	26	Bronze (96)	180	8,6
2015.6180.0810.2700.496	*TORCH/T8/ME_648/180-496 8.6W 26° 2700°K DALI	White (4)	2700	26	Bronze (96)	180	8,6
2015.6180.0810.4000.496	*TORCH/T8/ME_648/180-496 8.6W 26° 4000°K DALI	White (4)	4000	26	Bronze (96)	180	8,6
2015.6180.0810.496	*TORCH/T8/ME_648/180-496 8.6W 26° DALI	White (4)	3000	26	Bronze (96)	180	8,6



Article code	Name	Description	Colour	Driver's type	Watt (W)
1.1200EN1812	DALIGATE 48V CASAMBI - Box Nero	Interfaccia Bluetooth-DALI compatibile con sistemi Bluetooth CASAMBI - Consumo 8W	Black (2)	CASAMBI	8